


Apvalūs strypai:

- EN 10060,
- S235JR, S275JR, S355J2



D (mm)	Svoris (kg/m)	Skerspjūvio plotas (cm²)		D (mm)	Svoris (kg/m)	Skerspjūvio plotas (cm²)
8	0,395	0,503		50	15,40	19,6
10	0,617	0,785		55	18,70	23,8
12	0,888	1,13		60	22,20	28,3
14	1,21	1,54		65	26,00	33,2
16	1,58	2,01		70	30,20	38,5
18	2,00	2,54		75	34,70	44,2
20	2,47	3,14		80	39,50	50,3
22	2,98	3,80		85	44,50	56,7
24	3,55	4,52		90	49,90	63,6
25	3,85			95	55,60	70,9
26	4,17	5,31		100	61,70	78,5
28	4,83	6,16		110	74,60	95,0
30	5,55	7,07		120	88,80	113,0
32	6,31	8,04		130	104,00	133,0
34	7,13	9,08		140	121,00	154,0
35	7,55	9,62		150	139,00	177,0
36	7,99	10,20		160	158,00	201,0
38	6,90	11,30		170	178,00	227,0
40	9,86	12,60		180	200,00	254,0
42	10,90	13,90		190	223,00	284,0
45	12,50	15,90		200	247,00	314,0